

## Technical Specification

### ProGlove MARK 3

(multi range)

#### WIRELESS COMMUNICATION

BLUETOOTH RADIO FREQUENCY RANGE	Supports Bluetooth Low Energy 4.0, 4.1, 4.2, 5.0	
MAX RADIO-FREQU. POWER TRANSMITTED	< 20dBm	
TRANSMISSION RANGE	<b>3<sup>rd</sup> party device</b> Free field: 40 m (131 ft)** Indoor: 10-20 m (33-66 ft)**	<b>ProGlove Gateway</b> Free field: 70 m (230 ft)** Indoor: 30-40 m (100-130 ft)**
	**may decrease in industrial environments (e.g. due to walls, metal shelving, machines)	

#### BARCODE DECODING CAPABILITIES

1D	Auto decodes all standard 1D codes including GS1 DataBar linear codes et al.
2D	PDF417, MicroPDF417, Data matrix, QR Code, Micro QR Code, Aztec, MaxiCode, et al.
POSTAL	US PostNet, US Planet, UK Postal, Australia Postal, Japan Postal, Dutch Postal (KIX) et Al.

#### ELECTRICAL PROPERTIES

BATTERY	670 mAh, Lithium polymer (rechargeable)
CHARGING TIME	2 hours with ProGlove Charging Station
OPERATING TIME / SCANS	approx. 12000 scans depending on the application and environmental conditions

#### MECHANICAL PROPERTIES

DIMENSIONS	50 x 45 x 17 mm (1.47 x 1.77 x 0.67 in)
WEIGHT	39 g (1.38 oz)

#### ENVIRONMENTAL CONDITIONS

DROP RESISTANCE	Resists several drops from 2 m (6.5 ft) onto concrete
TUMBLES	2000 tumbles from 0.5 m
PROTECTION AGAINST DUST AND WATER	IP 65
TEMPERATURE	Operating Temperature: -20°C - 50°C (-4°F - 122°F) Charging Temperature: 5°C - 40°C (41°F - 104°F) Storage Temperature: -20°C - 60°C (-4°F - 140°F)
HUMIDITY	5% - 95% non condensing
ELECTROSTATIC DISCHARGE (ESD)	±8kVdc air discharge ±4kVdc contact discharge

#### INTERFACES

BLUETOOTH	HID Profiles
ANDROID	HID, Insight Mobile (Android) (App/SDK)
IOS	HID, Insight Mobile (iOS) (SDK)
USB	ProGlove Gateway

#### SCANNER PROPERTIES

RESOLUTION	2688 x 1520
READING FIELD OF VIEW	Horizontal: 37°, vertical: 21°
SKEW, PITCH & ROLL	Skew tolerance: ±60° Pitch tolerance: ±60° Roll tolerance: 360°
AMBIENT LIGHT	0 - 107,639 lux
AIMER	Green Laser 520nm

#### UTILITIES & ACCESSORIES\*

CONFIGURATION & DEVICE MANAGEMENT	<a href="https://insight.proglove.com">https://insight.proglove.com</a>
DIGITAL DOCUMENTATION	<a href="https://docs.proglove.com">https://docs.proglove.com</a>
ANDROID INTEGRATION	Insight Mobile: Provides a full featured integration for Android enterprise applications.
GATEWAY INTEGRATION	ProGlove Gateway: Hardware connector to enable the full capabilities of the ProGlove Ecosystem via USB-Interface.
TRIGGER	Scanner can be triggered only with ProGlove wearables (Hand Strap, Index-Trigger, Reel et al.)

\*More Information on [www.proglove.com](http://www.proglove.com)

#### SCAN RANGES

Minimum distance determined by symbol length, scan-angle and environmental conditions (e.g. lightning, printing quality, contrast et al.).

#### MULTI RANGE

3 mil Code 39	Near Distance: 2.7 in./6.9 cm; Far Distance: 16.2 in./41.1 cm
5 mil Code 39	Near Distance: 2.5 in./6.4 cm; Far Distance: 26.6 in./67.6 cm
5 mil PDF417	Near Distance: 2.8 in./7.1 cm; Far Distance: 19.6 in./49.8 cm
6.7 mil PDF417	Near Distance: 2.6 in./6.6 cm; Far Distance: 25.6 in./65.0 cm
10 mil DataMatix	Near Distance: 2.2 in./5.6 cm; Far Distance: 27.1 in./68.8 cm
100% UPCA (13 mil)	Near Distance: 2.5 in./6.4 cm; Far Distance: 71 in./180 cm
15 mil Code 128	Near Distance: 7.2 in./18.2 cm; Far Distance: 72 in./182.9 cm
20 mil Code 39	Far Distance: 109 in./276.9 cm
55 mil Code 39	Far Distance: 293 in./744.2 cm
100 mil Code 39	Far Distance: 554 in./1407.2 cm
100 mil DataMatrix	Far Distance: 270 in./685.8 cm

#### WARRANTY & SLA

WARRANTY	12 months factory warranty
PROGLOVE CARE	36 and 60 months maintenance contracts available. For more information please contact your ProGlove representative or visit <a href="https://proglove.com">https://proglove.com</a>

#### SAFETY & REGULATORY

RADIO AND ELECTROMAGNETIC COMPATIBILITY	EU: 2014/53/EU Radio Equipment Directive (RED) FCC ID: 2A0JL-MARK-3 IC: 23450-MARK3
ELECTRICAL SAFETY	EU: acc. to 2014/53/EU Radio Equipment Directive (RED) EN 62368-1:2014 + A11:2017  INTERNATIONAL: IEC 62368-1:2014  US: UL 62368-1 and CAN/CSA C22.2 No. 62368-1
LASER CLASSIFICATION	Multi range: According to EN 60825-1:2014 and IEC 60825-1 (Ed. 3.0) Laser class 2 device. Caution Laser Radiation - Do not stare into beam.
ENVIRONMENTAL	RoHS Directive 2011/65/EU; Amendment 2015/863, REACH SVHC 1907/2006, WEEE

#### COUNTRY CERTIFICATION

Regulatory markings are affixed to the device, indicating that the radio modules are approved for use in the following regions: European Economic Area\*, Canada, United States of America, United Mexican States, China.

Detailed information on the regulatory markings can be found in the Declaration of Conformity (DoC) at [www.proglove.com](http://www.proglove.com)

\*CE is valid in the European Economic Area and additional countries: Austria, Belgium, Bulgaria, Croatia, Republic of Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, United Kingdom, Iceland, Liechtenstein, Switzerland and Norway.



**BSR idware GmbH**

Jakob-Haringer-Str.3

A-5020 Salzburg

<https://www.bsr.at>

[sales@bsr.at](mailto:sales@bsr.at)